



# NEW UV HYBRID PRINTER

## HUV-2000S Series

—  
Up to 72 sqm/h

4/5/6 Color

Negative Pressure System

Epson i3200-U Heads

2m / 2.6m / 3.2m




**PRECISIONCORE**  
PRINTHEAD  
powered by **EPSON**

## ● Features




### PrecisionCore Technology

Equipped with Epson latest industrial level i3200-U printheads, powered by advanced PrecisionCore technology, guarantee the high resolution, high efficiency and high stability production.




### Negative Pressure System

Two advanced separate negative pressure systems. Simply and effectively ensure the continuous ink flow, and easy maintenance for multi-heads equipment.




### Pneumatic media press bar & Alignment pins

Guarantee the high accuracy media stepping during printing.



### Electronic Controlled Vacuum Platform

Independent design of the printer vacuum platform. Four vacuum zones are electronic controlled. Convenient, high efficiency, energy saving.



### Anti-collision System

Printer will automatically stop when the carriage hit any unexpected object during working, and support continuing printing from the interruption part, reduce the material waste.

- ★ Well-designed machine structure, excellent for printing of both roll material, and regular rigid material.
- ★ Mature time-set stirring system for white ink, effectively decrease the problems caused by white ink precipitation.
- ★ Branded accessories are used for high attrition area. Greatly increased the lifetime and stability of the machine. For example, the Hiwin guide rail, German Iigus drag chain, Italian Megadyne belt.



## ● Specification

Model No.	HUV-3200S	HUV-2600S	HUV-2000S	
Printing Head	4 × Epson i3200-U	4 × Epson i3200-U	2 × Epson i3200-U (Can be upgraded to be 4 heads)	
Resolution	2400 dpi MAX			
Media	Width	3200 mm MAX	2600 mm MAX	2000 mm MAX
	Type	Acrylic, Wood, PVC Board, KT Board, Cardboard, Canvas, Leather, Carpet, Vinyl, Paper, PP Sheet, PVC, ABS ...		
	Thickness	0-5 cm		
Ink	Type	UV Ink		
	Color	CMYK/CMYK+W/CMYK+W+V	CMYK/CMYK+W/CMYK+W+V	CMYK/CMYK+W
	Curing	High Quality Water Cooling UV-LED Lamp		
Speed	Draft	72 m <sup>2</sup> /h	64 m <sup>2</sup> /h	35 m <sup>2</sup> /h
	Production	36 m <sup>2</sup> /h	32 m <sup>2</sup> /h	18 m <sup>2</sup> /h
	Quality	20 m <sup>2</sup> /h	18 m <sup>2</sup> /h	10 m <sup>2</sup> /h
Ink Supply System	Two advanced separate negative pressure systems (One for color and varnish, One for white).			
Cleaning	Press one button to flush the head automatically			
Feed & TakeUp	Automatic Media Feeding (Standard) & Take up System (Standard)			
Rip Software	MainTop (Standard) / Photoprint (Optional)			
Connector	USB 3.0			
Power	AC 110V / 220V ± 5%, 16A, 50/60Hz ± 1, 1500W MAX			
Size	Machine	L5017 x W2817 x H1455mm	L4417 x W2817 x H1455mm	L3817 x W2817 x H1455mm
	Packing	L5117 x W1224 x H1685mm	L4517 x W1224 x H1685mm	L3917 x W1224 x H1685mm
Weight	Machine	1200 KG	1050 KG	850 KG
	Packing	1550 KG	1350 KG	1100 KG

Specifications are subject to change without notice.