



# A3 DTG T-shirt Printer

**DIRECT TO GARMENT** 



**€asy to Use** 易于使用

White Circulation 白墨循环

> Super Reliable 超稳定

> > High Speed 速度快



## **A3 DTG Print∈r**

### TP-300i & TP-600i

#### • Features 特点



SinoColor System. Much more professional and more stable than desktop modified printer. Control the color freely.

SinoColor System 相比改装机更多功能可实现, 色彩控制更加随心所欲。



Well-designed adjustable platform. The good smoothness of platform and high accuracy printing are quaranteed.

可调节的平台设计保证平台始终处于平整状态以 达到最高的打印精度。



Well-designed touch screen. Easily Adjust platform position.

精心设计的触摸屏, 轻松调整平台位置。



Branded circuit breaker to protect the safety of the whole electronic system.

漏电保护开关保护整机电路系统安全。



Maximumly use mold to produce machine components to achieve amazing resolution.

最大程度模具化生产设备组件以达到最高的



#### ● **Specification** 参数

Model N	0.	型号	TP-300i	TP-600i
Printhead		打印喷头	2× Epson Heads	2× Epson Heads
Resolution		打印精度	1440dpi	
Max Speed		打印速度	2 minutes for one T-shirt	
Print Head Height		喷头高度	10 cm Max	
Printing Size		打印尺寸	30 × 40 cm Max	40 × 60 cm Max
Print Direction		打印方向	Intelligence double side	
Print Method		打印方法	micro piezo print technology, intelligence drops transformation technology	
Height Adjust		高度调节	Electric	
Distance of Print Head Printing		ad Printing	1-3 mm (1 mm is the best)	
Ink Color		墨水颜色	4 colors (CMYK) or 5 colors (CMYK,W)	
Ink Supply System		供墨系统	CISS	
Ink Consumption		墨水消耗	15-20 ml / squre meter (1 liter print about 500PCS t-shirt)	
Min Ink Drop Size		墨滴大小	< 1.5 PL	
Interface		输入接口	USB3.0	
Rip Software		图像处理	Maintop (Standard)/ Photoprint (Optional)	
Working Environment 工作环境		it 工作环境	Temperature 18-30 Celsius, Humidity 30-70 RH, Clean room, Low dust, Less sun light	
Power 电源输入		电源输入	AC 110/220 V, 50 Hz/60 Hz	
Size &	Machine	机器	L670mm W565mm H635mm / 90KG	
Weight	Packing	包装	L745mm W745mm H730mm / 100KG	

Specifications are subject to change without notice. 以上参数可能随机器版本改变,请以厂家最新数据为准。