

Epson Series UV Roll to Roll Printer

1.8米UV卷材打印机 — 高性价比之选

Dual Heads
双喷头

4/5/6/7-Color
4/5/6/7色写真

Variable Dot
可变墨滴

White Optional
白色可选

2 Sizes & 2 Print-head Configurations Available 提供两种尺寸和两种喷头配置



● Features 特点



Different Printhead Available
Equipped Epson F1080 or DX5 or i3200 Head. 4 colors and 6 colors models are optional.

爱普生DX5和F1080,i3200 三种喷头可选
根据你的需求来选择4色或者6色输出




Water Cooling UV-LED Lamp
It is one of the world's top UV-LED, long lifespan, low heat, and instant on-off

水冷UV-LED灯
装备世界顶级的UV-LED, 寿命长, 发热低, 即时开关



Variable Dot Print Technology
Permitting the printer to provide smooth gradations, exceptional solid colors and optimum image quality in all print modes
可变墨滴技术
使打印画面的颜色过渡更加自然, 实现高质量成像



Anti-collision Function
Anti-collision system is equipped to protect the printhead and carriage all the time

防撞功能
标配防撞装置, 支持中断处续打



Integrated Take Up System
It offers adjustable roll widths, making it suitable for various sized media rolls and applications

收放布系统
卷幅宽度可调, 适用于众多尺寸的卷材

- ★ High-density UV curable ink produces rich, vibrant colors on coated or uncoated media
高品质UV固化墨水在涂层或非涂层材料上实现丰富而鲜明的色彩
- ★ Durable, scratch-resistant and virtually odorless, Up to three years outdoor durability without lamination
画面持久, 耐刮擦, 无异味, 不覆膜长达三年的户外耐候性
- ★ Branded parts are used for high attrition area. Greatly increased the lifetime and stability of the machine.
For example, Hiwin guide rail, German Igus drag chain, Italian Megadyne belt.
高损耗处皆使用高等级配件, 极大提升设备使用寿命和稳定性



● Specification 参数

| Model No. | 型号 | UV-740 | UV-740E |
|---------------|---------------|---|-----------------------------|
| Printing Head | 打印喷头 | 2 × Epson DX5 | 2 × Epson F1080 |
| Resolution | 打印精度 | 1440 dpi MAX | |
| Media 耗材 | Width 耗材宽度 | 1800 mm MAX | |
| | Type 耗材种类 | Canvas, Garment, Leather, PET Film, Reflective Film, Soft Ceiling Film & More Flexible Material Etc. 天花软膜、灯布、车贴、服装、皮革、PET膜、反光膜以及其他众多卷材 | |
| Speed 速度 | Draft 草图模式 | 14 m ² /h | 15 m ² /h |
| | Standard 标准模式 | 10 m ² /h | 12 m ² /h |
| | Quality 精细模式 | 6 m ² /h | 8 m ² /h |
| Ink 墨水 | Type 墨水类型 | UV Ink | |
| | Color 墨水颜色 | CMYK / CMYK + W | CMYK Lc Lm / CMYK Lc Lm + W |
| | Curing 墨水固化 | High Quality Water Cooling UV-LED Lamp 水冷UV-LED灯 | |
| Cleaning | 清洗系统 | Automatic Cleaning, Anti-Clogging Flash Function & Capping System 自动清洗、闪喷、封喷头 | |
| Feed & TakeUp | 收放布 | Automatic Media Feeding (Standard) & Take up System (Optional) 自动收放布 | |
| Rip Software | 操作软件 | Main Top (Standard) / Photo Print (Optional) | |
| Connector | 连接方式 | USB 3.0 | |
| Power | 电力消耗 | AC 110V / 220V ± 5%, 16A, 50/60Hz ± 1, 1500W MAX | |
| Size 尺寸 | Machine 机器尺寸 | L2960 x W800 x H1270 mm | |
| | Packing 包装尺寸 | L3210 x W1000 x H740 mm | |
| Weight 重量 | Machine 机器重量 | 320 KG | |
| | Packing 机器重量 | 400 KG | |

Specifications are subject to change without notice. 以上参数可能随机器版本改变, 请以厂家最新数据为准。