

Eco Solvent Printer

1.8m F1080/DX5 Printhead

1.8米 爱普生 F1080/DX5 户内外写真机

Dual Heads 双喷头

4/6 Color 4/6色写真

Variable Dot 可变墨滴

3-Stage Heater 三段加热

2 Sizes & 3 Print-head Configurations Available
提供两种尺寸和三种喷头配置



● Features 特点



Different Printhead Available
Equipped Epson F1080 or DX5 or i3200 Head. 4 colors and 6 colors models are optional.

爱普生DX5和F1080,i3200 三种喷头可选
根据你的需求来选择4色或者6色输出



Heating and Drying System
Front and middle and rear heating system and front drying fan are standard equipped to help dry the printed material fast.

加热和冷却系统
标配前中后加热系统和前置冷却风扇



Anti-collision Function
Anti-collision system is equipped to protect the printhead and carriage all the time

防撞功能
标配防撞装置，支持中断处续打



Branded parts
Greatly increased the lifetime and stability of the machine. For example,Hiwin guide rail,German Igus drag chain, Italian Megadyne belt.

高损耗处皆使用高等级配件
极大提升设备使用寿命和稳定性



Variable Dot Print Technology
Permitting the printer to provide smooth gradations, exceptional solid colors and optimum image quality in all print modes

可变墨滴技术
使打印画面的颜色过渡更加自然，实现高质量成像

- ★ New look has heavier, larger structure, and wider printing platform
新造型更加厚重大气，更宽的打印平台
- ★ Aluminous carriage girder ensures high accuracy of carriage movement
铝制小车梁，精度有保障
- ★ Dual feeding bar for loading heavy media
双送纸杆，以承受更重的耗材
- ★ Optional infrared heater for drying prints quickly
选配红外加热装置，画面极速烘干
- ★ Integrated temperature controller
一体式温控仪



● Specification 参数

Model No.	型号	SJ-740E	SJ-740	SJ-740i
Printhead	喷头	2 x Epson F1080	2 x Epson DX5	1 x Epson DX5
Resolution	精度	1440dpi max		
Ink Color	色彩	C M Y K / C M Y K Lc Lm	C M Y K	C M Y K
Media 耗材	Size 尺寸	1.8 meter		
	Types 种类	Flex Banner , Vinyl, One Way Vision, Banner Cloth, Window Film, Mesh Etc. 灯箱布，车贴，单透贴，条幅布，玻璃贴膜，网格布等		
Speed 速度	4 Pass 标准	32 sqm/h	30 sqm/h	15 sqm/h
	6 Pass 精细	24 sqm/h	22 sqm/h	11 sqm/h
	8 Pass 照片	18 sqm/h	16 sqm/h	8 sqm/h
Ink Type	墨水	Eco Solvent Ink 弱溶剂墨水		
Ink Droplet	墨滴	1.5-21pl variable 1.5至21皮升可变墨滴		
Cleaning	清洗	Automatic Cleaning, Anti-Clogging Flash Function & Capping System 自动清洗、闪喷、封喷头		
Feed & take up	收放布	Automatic Media Feeding (Standard) & Take up System (Optional) 自动收放布		
Environment	环境	Temperature: 20-28 °C, Humidity: 40%-60%		
Rip Software	软件	Maintop (Standard) / Photoprint (Optional)		
Interface	接口	USB3.0		
Power	电源	Machine 50/60HZ, 110 / 220V, 1200W		
Size & Weight	Machine 机器	L3100 x W780 x H1500 mm / 280 KG		
	Packing 包装	L3210 x W1000 x H740 mm / 400 KG		

Specifications are subject to change without notice. 以上参数可能随机器版本改变，请以厂家最新数据为准。