

Eco Solvent Printer

3.2m F1080 / DX5 Printhead

3.2米 爱普生 F1080 / DX5 户内外写真机

2 Sizes Available

提供两种尺寸

Dual Heads 双喷头

4/6 Color 4/6色写真

Variable Heads 可变墨滴

3-stage Heater 三段加热



Eco Solvent Printer | SJ-1260 & SJ-1260C

● Features 特点



Different Printhead Available
Equipped Epson F1080 or DX5 or i3200 Head. 4 colors and 6 colors models are optional.


爱普生DX5和F1080,i3200 三种喷头可选
根据你的需求来选择4色或者6色输出



Well Designed Feeding System
Two sets media feeding system are standard equipped. Enable to install both 3.2m heavy banner and 2 rolls small size paper.
精心设计的放布系统
配备两套放布系统，方便日常操作



Anti-collision Function
Anti-collision system is equipped to protect the printhead and carriage all the time
防撞功能
标配防撞装置，支持中断处续打



Branded parts
Greatly increased the lifetime and stability of the machine. For example,Hiwin guide rail,German Iigus drag chain, Italian Megadyne belt.
高损耗处皆使用高等级配件
极大提升设备使用寿命和稳定性



Variable Dot Print Technology
Permitting the printer to provide smooth gradations, exceptional solid colors and optimum image quality in all print modes
可变墨滴技术
使打印画面的颜色过渡更加自然，实现高质量成像

- ★ New look has heavier, larger structure, and wider printing platform
新造型更加厚重大气，更宽的打印平台
- ★ Big Functional Control Panel. Adopts the latest program Intelligent Error Auto-Detection boards, it can guide user to find solution very quickly
超大多功能控制面板。采用智能报错，指导用户快速发现问题
- ★ IGUS Drag Chain from Germany. A guarantee of quality, takes the printer stability to a new level. Effectively protect ink tube and cables
德国Iigus拖链。保证高质。有效保护墨管和线路。提高机器稳定性
- ★ LED lamp strip is equipped, users could check out the print result more easily
配备LED灯条。帮助用户更好的查看打印效果
- ★ Optional infrared heater for drying prints quickly
选配红外加热装置，画面极速烘干



● Specification 参数

| Model No. | 型号 | SJ-1260E | SJ-1260 |
|----------------|------------|--|---------------|
| Printhead | 喷头 | 2 x Epson F1080 | 2 x Epson DX5 |
| Resolution | 精度 | 1440dpi max | |
| Ink Color | 色彩 | C M Y K / C M Y K Lc Lm | C M Y K |
| Media 耗材 | Size 尺寸 | 3.2 meter | |
| | Types 种类 | Flex Banner , Vinyl, One Way Vision, Banner Cloth, Window Film, Mesh Etc. 灯箱布, 车贴, 单透贴, 条幅布, 玻璃贴膜, 网格布等 | |
| Speed 速度 | 4 Pass 标准 | 36 sqm/h | 34 sqm/h |
| | 6 Pass 精细 | 26 sqm/h | 24 sqm/h |
| | 8 Pass 照片 | 20 sqm/h | 18 sqm/h |
| Ink Type | 墨水 | Eco Solvent Ink 弱溶剂墨水 | |
| Ink Droplet | 墨滴 | 1.5-21pl variable | 1.5至21皮升可变墨滴 |
| Cleaning | 清洗 | Automatic Cleaning, Anti-Clogging Flash Function & Capping System 自动清洗、闪喷、封喷头 | |
| Feed & take up | 收放布 | Automatic Media Feeding (Standard) & Take up System (Optional) 自动收放布 | |
| Environment | 环境 | Temperature: 20-28 C , Humidity: 40%-60% | |
| Rip Software | 软件 | Maintop (Standard) / Photoprint (Optional) | |
| Interface | 接口 | USB 3.0 | |
| Power | 电源 | Machine 50/60HZ, 110 / 220V, 1500W | |
| Size & Weight | Machine 机器 | L4360 x W780 x H1500 mm / 480 KG | |
| | Packing 包装 | L4610 x W1000 x H740 mm / 640 KG | |

Specifications are subject to change without notice. 以上参数可能随机器版本改变，请以厂家最新数据为准。