Epson Series
UV Roll to Roll Printer

UV卷材打印机 — 高性价比之选

4/5-Color	Dual Heads	Variable Dot	White Optional
4/5色写真	双喷头	可变墨滴	白色可选

Epson Official Supplied i3200-U Printheads　配备爱普生官方原装i3200-U喷头

SINO COLOR

PRECISIONCORE
PRINTHEAD
i3200-U powered by EPSON

UV Roll to Roll Printer | UV-740S

● Features 特点

Epson Official Supplied Printheads
Latest Epson Industrial Printhead i3200-U Equipped. Focus on super fast speed printing.

最新的爱普生i3200-U工业级喷头, 专注高速打印

Water Cooling UV-LED Lamp
It is one of the world's top UV-LED, long lifespan, low heat, and instant on-off

装备世界顶级的UV-LED, 寿命长, 发热低, 即时开关

Variable Dot Print Technology
Permitting the printer to provide smooth gradations, exceptional solid colors and optimum image quality in all print modes

使打印画面的颜色过渡更加自然, 实现高质量成像

Anti-collision Function
Anti-collision system is equipped to protect the printhead and carriage all the time

标配防撞装置, 支持中断处续打

Integrated Take Up System
It offers adjustable roll widths, making it suitable for various sized media rolls and applications

卷幅宽度可调, 适用于众多尺寸的卷材

★ High-density UV curable ink produces rich, vibrant colors on coated or uncoated media
高品质UV固化墨水在涂层或非涂层材料上实现丰富而鲜明的色彩

★ Durable, scratch-resistant and virtually odorless, more than three years outdoor durability without lamination
画面持久, 耐刮擦, 无异味, 不覆膜长达三年的户外耐候性

★ Branded parts are used for high attrition area. Greatly increasedthe lifetime and stability of the machine. For example,Hiwin guide rail,German Igus drag chain, Italian Megadyne belt
高损耗处皆使用高等级配件, 极大提升设备使用寿命和稳定性

● Specification 参数

Model No.		型号	UV-740S
Printing Head		喷头	2 × Epson i3200-U
Resolution		精度	2400 dpi MAX
Media 耗材	Width	宽度	1800 mm MAX
	Type	种类	Canvas, Garment, Leather, PET Film, Reflective Film, Soft Ceiling Film & More Flexible Material Etc.
Ink 墨水	Type	类型	UV Ink
	Color	颜色	C M Y K / C M Y K + W
	Curing	固化	High Quality Whater Cooling UV-LED Lamp
Speed 速度	Test Color Mode		Color Mode
	Draft	草图	40 m²/h
	Production	标准	20 m²/h
	Quality	精细	12 m²/h
Cleaning		清洗	Automatic Cleaning, Anti-Clogging Flash Function & Capping System
Feed & TakeUp		收放布	Automatic Media Feeding (Standard) & Take up System (Optional)
Rip Software		软件	Main Top(Standard) / Photo Print(Optional)
Connector		接口	USB 3.0
Power		电源	AC 110V / 220V ± 5%, 16A, 50/60Hz ± 1, 1500W MAX
Size 尺寸	Machine	机器	L2960×W800×H1270 mm
	Packing	包装	L3210×W1000×H740 mm
Weight 重量	Machine	机器	320 KG
	Packing	包装	400 KG