

UV Roll To Roll Printer

4/6/8 Printheads

Variable Dot

4/5/6/7/8 Colors

White & Varnish

INDUSTRIAL GRADE



● Features 特点




Precisioncore Technology
Machine can use Epson i3200-U print-head, powered by advanced precisioncore technology, born for speed and resolution.

爱普生i3200-U 喷头可选，采用Precisioncore技术，为速度而生



Embossment effect printing
Maximum 5 layer printing(with DX8 print-head), create amazing embossing effect for your image.

最高5层的画面打印，铸就画面超高立体感




Negative Pressure System
Two advanced separate negative pressure systems. Simply and effectively ensure the continuous ink flow, and easy maintenance for multi-heads equipment.

配置高级的负压系统。稳定供墨，简化多头设备维护。



Dual guide rail
Dual guide rail configuration, guarantee the stability of long time running.

双导轨设计，提高设备长时间运行的稳定性



Anti-collision System
Printer will automatically stop when the carriage hit any unexpected object during working, and support continuing printing from the interruption part, reduce the material waste.

小车遇撞击自动停止，并支持中断处续打，减少意外带来的材料浪费

★ Well-designed tension type material feeding and take-up system. Ensure the high accuracy of material stepping.

精心设计的张力收放布系统，精确走步

★ Mature time-set stirring system for white ink, effectively decrease the problems caused by white ink precipitation.

成熟的白墨定时搅拌装置，有效防止UV白墨沉淀

★ Elegant and sleek appearance design, not only an advanced printing equipment, but also a decoration for the company.

简约大气的外观设计



● Specification 参数

Model No.	型号	UR-2000E	UR-2000S
Printing Head	打印喷头	6 × Epson DX8	4 × Epson i3200-U
Resolution	打印精度	1440 dpi MAX	
Media 耗材	Width 耗材宽度	2000 mm MAX	
	Type 耗材种类	Canvas, Garment, Leather, PET Film, Reflective Film, Soft Ceiling Film & More Flexible Material Etc. 天花软膜、灯布、车贴、服装、皮革、PET膜、反光膜以及其他众多卷材	
Speed 速度	Color Mode 颜色模式	3×W + 2×CMYK Lc Lm + 1×Varnish	CMYK
	Draft 草图模式	6 m ² /h	108 m ² /h
	Production 标准模式	4.5 m ² /h	80 m ² /h
	Quality 精细模式	3.5 m ² /h	54 m ² /h
Ink 墨水	Type 墨水类型	UV Ink	
	Color 墨水颜色	CMYK LC LM + W + V	CMYK/CMYK + W
	Curing 墨水固化	High Quality Whater Cooling UV-LED Lamp 水冷UV-LED灯	
Ink Supply System	供墨系统	Two advanced separate negative pressure systems (One for color and varnish, One for white).	
Cleaning	清洗系统	Automatic Cleaning, Anti-Clogging Flash Function & Capping System 自动清洗、闪喷、封喷头	
Feed & TakeUp	收放布	Automatic Media Feeding (Standard) & Take up System (Standard) 自动收放布	
Rip Software	操作软件	Photoprint	
Connector	连接方式	USB 3.0	
Power	电力消耗	AC 110V / 220V ± 5%, 16A, 50/60Hz ± 1, 1500W MAX	
Size 尺寸	Machine 机器尺寸	L3770 x W920 x H1710 mm	
	Packing 包装尺寸	L3870 x W1020 x H1940 mm	
Weight 重量	Machine 机器重量	850 KG	
	Packing 机器重量	1100 KG	

Specifications are subject to change without notice. 以上参数可能随机器版本改变，请以厂家最新数据为准。